



PLTC label tape

- Tape, permanent or removable
- Print with thermal transfer printer
- Perfect for component marking

A soft and flexible universal tape, for indoor and outdoor use.

Excellent resistance to moisture, alcohols and oil

Print the continuous tape in requested length via EOS or MK10 thermal transfer printer and Partex software Promark Creator.

General information

The most significant advantage and potential of the PLTC label is its continuous form, which enables to design and print labels of any length. Available in different height..

Vinyl label is characterized by high adhesion and is a perfect solution for rough surfaces and no straight shapes.

Durable acrylic adhesive allows using the tape on many surfaces, including stainless steel and glass.

UV resistance material.

Technical information

- Material: Vinyl
- Temperature: -40°C to +80°C
- Min application temperature: +2°C
- Standard colors: white and yellow. Others on request: red, blue, green, orange, brown, black and transparent.
- Adhesive: permanent Acrylic adhesive
- Expiry date: 24 month at +21°C and 50% RH.



Article No	Description	Height mm	Color	Packaging m/reel
PLTC009000D*VR	Tape, removable	9	yellow, white	100
PLTC009000D*VP	Tape, permanent	9	yellow, white	100
PLTC012000D*VP	Tape, permanent	12	yellow, white	100
PLTC025000D*VP	Tape, permanent	25	yellow, white	60
PLTC050000D*VP	Tape, permanent	50	yellow, white	30
PLTC100000D*VP	Tape, permanent	100	yellow, white	30

* Color: Yellow=4, White=9 (standard colors)